

Installation of Reflective Foil Insulation into the Roof. Commercial Roof Installation (Building Class 2 and 9)

1. Start installing Green Insulation™ from gutter.
2. Roll out Green Insulation™ across the top of battens or purlins.
3. Allow Green Insulation™ to sag to achieve a nominal air space of 40mm between Green Insulation™ and roof sheeting.
4. Roll out the next roll of Green Insulation™ overlapping by 50mm.
5. Where overlapping is less than 50mm, use 75 mm wide reinforced aluminium tape to join.

6. Roof sheeting can be installed by screwing through Green Insulation™ to the battens or purlins.

Residential Roof Installation (Class 1 & 10 buildings, shed and carport)

1. Start installing Green Insulation™ from gutter.
2. Roll out Green Insulation™ across the top of battens or purlins.
3. Allow Green Insulation™ to sag to achieve a nominal air space of 40mm between Green Insulation™ and roof sheeting.
4. Roll out the next roll of Green Insulation™ overlapping by 150mm.
5. Where overlap is less than 150mm, use 75 mm wide reinforced aluminium tape to join.
6. Roof sheeting can be installed by screwing through Green Insulation™ to the battens or purlins

Note:

1. Where battens and purlins are not used, roll out Green Insulation™ reflective foil insulation across the top of rafters.
2. Where insulation is used as a sarking, allow sufficient fall for water to run off.
3. Higher R-values can be achieved by increasing the air space between Green Insulation™ and roof sheeting.

[Commercial Roof | Click here to download installation sheet](#)

[Residential Roof | Click here to download installation sheet](#)

Green Insulation offer a range of support services for their foil insulation products. Should you need support, please contact us. **PH. (07) 3200 6522**

Green Insulation operate 8am to 5pm Monday to Friday E.S.T. excluding public holidays. We suggest the following contacts may be of value.

Free Engineer support. Whether you are specifying reflective foil insulation or you need other technical advice, please contact us: engineer@greeninsulation.com.au

Green Insulation DO NOT print marketing materials in line with their environmental policy. However, we can supply electronic information and marketing materials or real samples of our reflective aluminium foil insulation, shed insulation and reflective foam insulation. Please contact us on **(07) 3200 6522**

Visitors always welcome. Please call in at 1/13 Meakin Road, Meadowbrook Qld. 4131